

Industrial 8X1G POE Unmanaged Industrial POE Switch

Model: VC-H-IPS08G



Introductions:

Product Description

VC-H-IPS08G is a self-developed Gigabit unmanaged Ethernet industrial PoE switch designed to meet the needs of industrial area and systems, and can operate stably for a long time in harsh usage environments. It provides 8 Gigabit RJ45 ports, and all ports support full wire speed forwarding. It is suitable for security monitoring wireless networking and other application scenarios.

VC-H-IPS08G industrial Ethernet PoE switch has excellent adaptability to industrial site environment (including mechanical stability, climate environment adaptability, electromagnetic environment adaptability, etc.), IP30 protection level, support for three redundant power supplies, low-power fanless cooling technology. Simple management model, plug-and-play, no configuration, easy to use. Suitable for intelligent transportation, rail transportation, power industry, mining, oil, shipping, metallurgy and green energy construction and other industrial scenarios to set up a cost-effective, stable and reliable communication network.

Features

1. Support IEEE 802.3i, 802.3u, 802.3, 802.3af, 802.3at.
2. Provide 8 10/100/1000Mbps RJ45 ports.
3. 8 POE ports support 802.3af/at , per port up to 30W Poe power budget.
4. IP30 protection can reduce the impact of dust.
5. Support MAC address auto-learning, auto-aging and aging time setting.
6. Support 4K MAC address.
7. Provides VLAN and broadcast storm suppression switches to adapt to various complex network environments.
8. Three power inputs, redundant backup, greatly improving the reliability of product power supply.
9. Aluminum alloy shell, sturdy and durable.
10. EMC high protection level, no fear of various harsh environments.

Hardware Specification

Protocol Standards	Support IEEE 802.3i, 802.3u, 802.3, 802.3af, 802.3at
Ports	8×10/100/1000Mbps RJ45 PoE ports
Indicator light	8 status indicators Link/ACT, PWR
Power input	DC input voltage 44V~57VDC, Input current 3A(MAX)
Fan Quantity	Fanless
Performance	Store-and-forward, MAC address table depth 4K
Dimensions	153*114*38 mm
Switching Capacity	16Gbps
Forwarding Rate	11.904Mpps
MAC Address Table	4K
Packet Buffer Memory	1.5Mb
Installation	DIN-rail/wall mounting
Environment	Operating Temperature: -40C ~75C (-40 °F ~167 °F) Storage Temperature: -40C ~85C (-40 °F ~185 °F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing

Certification Standards_ EMS	IEC/EN 61000-4-2,Level 4 IEC/EN 61000-4-3,Level 4 IEC/EN 61000-4-4,Level 4 IEC/EN 61000-4-5,Level 3 IEC/EN 61000-4-6,Level 3 IEC/EN 61000-4-8,Level 5 IEC/EN 61000-4-9,Level 5 IEC/EN 61000-4- 10,Level 5
Packaging accessories	One VC-H-IPS08G Industrial Grade Switch Warranty Card User Manual